

CRIS



ANTI-SLIP CRYSTALLISER FOR TREATMENT OF MARBLE, MARBLE **COMPOSITION AND TERRAZZO FLOORS**

- Anti-slip effect tested by UL laboratories
- Eliminates porosity of calcareous floors
- Glossy effect



Crystalliser for calcareous floors. Eliminates micro-porosity by preventing dirt from penetrating. Excellent glossy effect. Registered with Underwriters Laboratories Inc. as anti-slip, high resistance product.

? HOW TO USE

After carefully removing wax using a wax stripper from the SUTTER PROFESSIONAL range, when the floor is completely dry, spray a small amount of the product (8-10 ml. per m2) directly onto the floor and use the single disc machine at a low speed (150/170 rpm minimum weight 45 kg) with steel wool pad (grade 00) until completely dry and polished (8-10 min per m2). Repeat if necessary. After treatment, damp mop with a disposal cloth.



DILUTION

Ready to use.

A TECHNICAL DATA

ASPECT: Opaque liquid

COLOR: Pink **PERFUME:** Floral **COV:** 5,10%

PH	Active substance [%]	Density (g/ml)	Pressure (bar)	Viscosity (cP)	Total dry residue [%]
1.5 ± 0.5	30 ± 2	1.14			



CRIS

(!) WARNINGS

Harmful if swallowed. Causes severe skin burns and eye damage. Harmful to aquatic life with long lasting effects. Wear eye protection. IF SWALLOWED: rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician. Contents MAGNESIUMHEXAFLUOROSILICATE.





WARNING

₽ NOTES

Do not use CRIS at temperatures below 10° C. Keep away from freezing. Sutter Professional cannot be considered liable for any damage due to improper product use.

Only for professional use. Safety data sheet available on request.

PACKAGING

 Code	Size	Quantity	Pallet
5427	Kg 5	4	9x4=36



